

INSTALLATION INSTRUCTIONS

OMNI HEEL-TOE SHIFTER LEVER FOR GL1800

6756 SATIN BLACK OR 6757 CHROME

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

⚠ WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

⚠ CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- | | | | |
|---|--------------------|---|--|
| 1 | Shift Lever | 1 | M8 X 1.25 X 45mm Button Head Cap Screw |
| 1 | Ball Joint Linkage | 1 | Top Hat Bushing |

YOU WILL ALSO NEED:

Metric combination wrench set, metric hex wrench and bit set, torque wrench, ft-lbs (Nm) torque wrench

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

STEP 2 Loosen the lock nut on the shift linkage located behind the existing shift lever.

STEP 3 Remove the existing pivot bolt that is fastening the existing shift lever to the motorcycle. Set it aside, it will not be reused.

STEP 4 Refer to PIC 2. Remove existing shift lever and hardware. Set all aside, they will not be reused.

STEP 5 Refer to PIC 3. Remove existing ball joint from shift linkage. Set it aside, it will NOT be reused.



KURYAKYN.COM

INSTALLATION INSTRUCTIONS

OMNI HEEL-TOE SHIFTER LEVER FOR GL1800

-CONTINUED-

STEP 6 Refer to PIC 4. Locate provided Ball Joint Linkage. Fasten it to the open end of the shift linkage. Do not fully tighten the hex nut on shift linkage yet, adjustments may need to be made later.

STEP 7 Refer to PIC 5. Locate provided heel-toe shift lever. On the backside of the shift lever, fasten the fastened ball joint linkage to the lower mounting hole of the shift lever. Fully tighten ball joint to shift lever.

Note: Be aware adjustments will need to be made for final desired position of shift lever.

STEP 8 Locate provided screw and top hat bushing bushing. Place the bushing onto the bolt.

STEP 9 Refer to PIC 5 and 6. Insert the bolt and bushing assembly in through the front-side of the mounting hole on the shift lever. Lightly fasten shift lever to the motorcycle.

STEP 10 Adjust the position of the shift lever as needed by unfastening the shift lever from the motorcycle and ball joint, and loosening or tightening the shift lever's ball joint on the shift linkage. Make small adjustments to the ball joint and then reattach the lever and test the position.

STEP 11 Once satisfied with the position of the shift lever, remove the shift lever and fully tighten the hex nut on the shift linkage. Apply a small amount of blue loctite to the threads of the ball joint, and fully fasten it to the backside of the shift lever.

STEP 12 Fully tighten the mounting bolt to properly secure the shift lever in place.

TORQUE VALUE OF MOUNTING BOLT:
16 FT-LBS (22NM)

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



PIC 4



PIC 5



PIC 6



FINAL



INSTALLATION INSTRUCTIONS

OMNI HEEL-TOE SHIFTER LEVER FOR GL1800

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM

454 COUNTY ROAD VV SOMERSET, WI 54025

PAGE 3

306756

DPF-MRK-003 REV B 1/16/20

